



SIDDARTHA INSTITUTE OF SCIENCE AND TECHNOLOGY, PUTTUR  
Siddharth Nagar, Narayanavanam Road – 517583

**QUESTION BANK (DESCRIPTIVE)**

**Subject with Code:** Heat & Mass Transfer (18ME0320)

**Branches:** ME

**Year & Sem:** III-B.Tech & I-Sem

**Regulation:** R18

**UNIT –I  
BASIC CONCEPTS**

<b>1</b>	<b>a</b>	What is Heat Transfer	[L1][CO1]	[2M]
	<b>b</b>	How is Heat Transferred	[L1][CO1]	[2M]
	<b>c</b>	What is Conduction?	[L1][CO1]	[2M]
	<b>d</b>	What is Convection Equation	[L1][CO1]	[2M]
	<b>e</b>	What is Fourier's law	[L1][CO1]	[2M]
<b>2</b>	a)	List the basic laws which govern the heat transfer	[L1][CO1]	[5M]
	b)	Name and explain the mechanism of heat transfer	[L1][CO1]	[5M]
<b>3</b>	a)	What is Fourier's law of conduction? State the assumption and essential feature of it	[L1][CO1]	[5M]
	b)	Define the following terms. i).Thermal Conductivity ii).Thermal Resistance	[L1][CO1]	[5M]
<b>4</b>	a)	Distinguish between conduction, convection and radiation modes of heat transfer	[L3][CO1]	[5M]
	b)	Calculate the rate of heat transfer per unit area through a copper plate 45 mm thick, whose one face is maintained at 350 °C and the other face at 50 °C. Take thermal conductivity of copper as 370 W/m °C.	[L4][CO1]	[5M]
<b>5</b>	a)	What is conduction heat transfer? Explain its parameters	[L1][CO1]	[5M]
	b)	A plane wall is 150 mm thick and its wall area is 4.5 m <sup>2</sup> . If its conductivity is 9.35 W/m °C and surface temperature are steady at 150 °C and 45 °C, determine i).Heat transfer across the plane wall, ii).Temperature gradient in the flow direction	[L4][CO1]	[5M]
<b>6</b>	a)	What is convection heat transfer? Explain its parameters	[L1][CO1]	[5M]
	b)	A wire 1.5 mm diameter and 150 mm long is submerged in water at atmospheric pressure. An electric current passed through the wire and is increased until the water boils at 100 °C. Under the condition, if convective heat transfer coefficient is 4500W/m <sup>2</sup> °C. Find how electric power must be supplied to the wire to maintain the wire surface at 120 °C	[L4][CO1]	[5M]
<b>7</b>	a)	Write the laws of radiation? Explain its parameters	[L1][CO1]	[5M]
	b)	A surface having an area of 1.5 m <sup>2</sup> and maintained at 300 °C exchanges heat by radiation with another surface at 40 °C. The value factor due to the geometric location and emissivity is 0.52. Determine i).Heat loss by radiation ii).The value of thermal resistance iii).The value of equivalent convection coefficient	[L4][CO1]	[5M]
<b>8</b>		Derive the general heat conduction equation in Cartesian coordinate	[L3][CO1]	[10M]
<b>9</b>		Derive the general heat conduction equation in Cylindrical coordinate	[L3][CO1]	[10M]
<b>10</b>		Derive the general heat conduction equation in Spherical coordinate	[L3][CO1]	[10M]


**SIDDHARTHA INSTITUTE OF SCIENCE AND TECHNOLOGY, PUTTUR**

Siddharth Nagar, Narayanavanam Road – 517583

**QUESTION BANK (DESCRIPTIVE)**
**Subject with Code:** Heat & Mass Transfer (18ME0320)

**Branches:** ME

**Year & Sem:** III-B.Tech & I-Sem

**Regulation:** R18

**UNIT –II**
**ONE DIMENSIONAL STEADY STATE HEAT CONDUCTION, EXTENDED SURFACES  
& TRANSIENT HEAT CONDUCTION**

1	a	Define overall heat transfer co-efficient	[L1][CO2]	[2M]
	b	What is critical radius of insulation	[L][CO2]	[2M]
	c	Define Fin efficiency	[L][CO2]	[2M]
	d	Define Fin effectiveness	[L][CO2]	[2M]
	e	What is lumped heat analysis	[L][CO2]	[2M]
2	a)	Derive an expression for heat conduction through a composite wall	[L3][CO2]	[5M]
	b)	A reactor's wall, 320 mm thick, is made up of an inner layer of fire brick ( $k = 0.84 \text{ W/m } ^\circ\text{C}$ ) covered with a layer of insulation ( $k = 0.16 \text{ W/m } ^\circ\text{C}$ ). The reactor operates at a temperature of $1325 \text{ } ^\circ\text{C}$ and the ambient temperature is $25 \text{ } ^\circ\text{C}$ . Determine the thickness of fire brick and insulation which gives minimum heat loss.	[L4][CO2]	[5M]
3		A steam pipe of outside diameter 80 mm and 25 m long conveys 800 kg of steam per hour at a pressure of 22 bar. The steam enters the pipe with a dryness fraction of 0.99 and is to leave the other end of the pipe with the minimum dryness fraction of 0.97. This is to be accomplished by using a lagging material ( $k = 0.2 \text{ W/m } ^\circ\text{C}$ ), determine its minimum thickness to meet the necessary condition, if the temperature of the outside surface of lagging is $25 \text{ } ^\circ\text{C}$ . Assume that there is no pressure drop across the pipe and the resistance of the pipe material is negligible.	[L4][CO2]	[10M]
4	a)	Obtain the expression of heat conduction through hollow cylinder	[L3][CO2]	[5M]
	b)	A spherical shaped vessel of 1.4 m diameter is 90 mm thick. Find the rate of heat leakage, if the temperature difference between the inner and outer surface is $220 \text{ } ^\circ\text{C}$ . Thermal conductivity of the material of the sphere is $0.083 \text{ W/m } ^\circ\text{C}$ .	[L4][CO2]	[5M]
5	a)	Derive the expression for the overall heat transfer coefficient for a composite wall.	[L3][CO2]	[4M]
	b)	A cold storage room has walls made up of 220 mm of brick on outside 90 mm of plastic foam and finally 16 mm of wood on the inside. The outside and inside air temperatures are $25 \text{ } ^\circ\text{C}$ and $-3 \text{ } ^\circ\text{C}$ respectively. If the inside and outside heat transfer coefficients are 30 and $11 \text{ W/m}^2 \text{ } ^\circ\text{C}$ respectively the thermal conductivity of brick, plastic foam and wood are 0.99, 0.02 and $0.17 \text{ W/m } ^\circ\text{C}$ respectively. Then determine	[L4][CO2]	[6M]
	i.	The rate of heat removal by the refrigeration, if the total wall area is $85 \text{ m}^2$		
	c) ii.	The temperature of the inside surface of the brick		
6	a)	Derive an expression for heat conduction through a plane wall	[L1][CO2]	[5M]
	b)	Calculate the critical radius of insulation for asbestos ( $k = 0.172 \text{ W/m } ^\circ\text{C}$ ) surrounding a pipe and exposed to room air at 300 K with $h = 2.8 \text{ W/m } ^\circ\text{C}$ . Calculate the heat loss from a 475 K, 60 mm diameter pipe when covered with the critical radius of insulation and without insulation.	[L4][CO2]	[5M]
7	a)	What is lumped system analysis? Derive the expression for it	[L2][CO2]	[4M]
	b)	A 50 cm x 50 cm copper slab 6.25 mm thick has a uniform temperature of $300 \text{ } ^\circ\text{C}$ . Its temperature is suddenly lowered to $36 \text{ } ^\circ\text{C}$ . Calculate the time required for the plate to reach the temperature of $108 \text{ } ^\circ\text{C}$ . Take $\rho = 9000 \text{ kg/m}^3$ , $c = 0.38 \text{ kJ/kg } ^\circ\text{C}$ , $k = 370 \text{ W/m } ^\circ\text{C}$ and $h = 90 \text{ W/m}^2 \text{ } ^\circ\text{C}$ .	[L4][CO2]	[6M]

<b>8</b>	a) Write short note on transient heat conduction	[L1][CO2]	[4M]
	b) A steel ingot (large in size) heated uniformly to 745 °C is hardened by quenching it in an oil bath maintained at 20 °C. Determine the length of time required for the temperature to reach 595 °C at a depth of 12 mm. The ingot may be approximated as a flat plate. For steel ingot take $\alpha$ (thermal diffusivity) = $1.2 \times 10^{-5}$ m <sup>2</sup> /s.	[L4][CO2]	[6M]
<b>9</b>	a) Sketch various types of fins. Give examples of use of fins in various engineering applications	[L3][CO2]	[5M]
	b) Calculate the amount of energy required to solder together two very long pieces of bare copper wire 1.5 mm diameter with solder that melts at 190 °C. The wires are positioned vertically in air at 20 °C. Assume that the heat transfer coefficient on the wire surface is 20 W/m <sup>2</sup> °C and thermal conductivity of wire alloy is 330 W/m °C	[L4][CO2]	[5M]
<b>10</b>	a) Explain the fin effectiveness and fin efficiency	[L2][CO2]	[5M]
	b) A longitudinal copper fin ( $k = 380$ W/m °C) 600 mm long and 5 mm diameter is exposed to air stream at 20 °C. The convective heat transfer coefficient is 20 W/ m <sup>2</sup> °C. If the fin base temperature is 150 °C, determine i. The heat transferred, and ii. The efficiency of the fin	[L4][CO2]	[5M]


**SIDDARTHA INSTITUTE OF SCIENCE AND TECHNOLOGY, PUTTUR**

Siddharth Nagar, Narayanavanam Road – 517583

**QUESTION BANK (DESCRIPTIVE)**

Subject with Code: Heat &amp; Mass Transfer (18ME0320)

Branches: ME

Year &amp; Sem: III-B.Tech &amp; I-Sem

Regulation: R18

**UNIT –III**
**FREE CONVECTION & FORCED CONVECTION**

1	a	Define convection.	[L1][CO3]	[2M]
	b	What is meant by free or natural convection	[L1][CO3]	[2M]
	c	What is forced convection?	[L1][CO3]	[2M]
	d	What are the dimensionless parameters used in forced convection	[L1][CO3]	[2M]
	e	What is meant by laminar flow and turbulent flow?	[L1][CO3]	[2M]
2	a)	What is convective heat transfer? Distinguish between free and forced convection	[L1][CO3]	[5M]
	b)	Derive the expression for Reynolds number and how flows are determined by Reynolds number?	[L3][CO3]	[5M]
3		Air at 20 °C and at a pressure of 1 bar is flowing over a flat plate at a velocity of 3 m/s. If the plate is 280 mm wide and at 56 °C. Calculate the following quantities at x = 280 mm, given that properties of air at the bulk mean temperature °C are $\rho = 1.1374 \text{ kg/m}^3$ , $k = 0.02732 \text{ W/m } ^\circ\text{C}$ , $c_p = 1.005 \text{ kJ/kg K}$ , $\nu = 16.76 \times 10^{-6} \text{ m}^2/\text{s}$ , $Pr = 0.7$ i. Boundary layer thickness ii. Local friction coefficient iii. Average friction coefficient iv. Thickness of the boundary layer v. Local convective heat transfer vi. Average convective heat transfer vii. Rate of heat transfer by convection viii. Rate of convective heat transfer	[L4][CO3]	[10M]
4	a)	What is the physical significance of the Nusselt number? How is it defined	[L1][CO3]	[4M]
	b)	Assuming that a man can be represented by a cylinder 350 mm in diameter and 1.65 m high with a surface temperature of 28 °C. Calculate the heat he would lose while standing in a 30 km/h wind at 12 °C.	[L4][CO3]	[6M]
5	a)	Define Nusselt number, Prandtl number and their significance	[L1][CO3]	[4M]
	b)	Air stream at 24 °C is flowing at 0.4 m/s across a 100 W bulb at 130 °C. If the bulb is approximately by a 65 mm diameter sphere. Calculate i. The heat transfer rate, ii. The percentage of power lost due to convection	[L4][CO3]	[6M]
6		In a straight tube of 60 mm diameter, water is flowing at a velocity of 12 m/s. The tube surface temperature is maintained at 70 °C and the following water is heated from the inlet temperature 15 °C to an outlet temperature of 45 °C. taking the physical properties of water at its mean bulk temperature, Calculate the following: i. The heat transfer coefficient from the tube surface to the water ii. The heat transferred iii. The length of the tube	[L4][CO3]	[10M]
7	a)	Mention the empirical correlation of free convection	[L3][CO3]	[4M]
	b)	A vertical cylinder 1.5m high and 180mm in diameter is maintained at 100 °C in an atmosphere environment of 20 °C. Calculate heat loss by free convection from the surface of the cylinder. Assume properties of air at mean temperature as $\rho = 1.06 \text{ kg/m}^3$ , $\nu = 18.97 \times 10^{-6} \text{ m}^2/\text{s}$ , $c_p = 1.004 \text{ kJ/kg } ^\circ\text{C}$ and $k = 0.1042 \text{ kJ/mh } ^\circ\text{C}$	[L4][CO3]	[6M]
8	a)	Differentiate between laminar and Turbulent flow.	[L3][CO3]	[4M]
	b)	A horizontal plate measuring 1.5 m x 1.1 m and at 215 °C, taking upward is placed in still air at 25 °C. Calculate the heat loss by natural convection. The convective film coefficient for free convection is given by the following empirical relation $h = 3.05(T_f)^{1/4} \text{ W/m}^2 \text{ } ^\circ\text{C}$ . where $T_f$ is the mean film temperature in degree Kelvin	[L4][CO3]	[6M]
9		A cylinder body of 300 mm diameter and 1.6 m height is maintained at a constant temperature of 36.5 °C. The surrounding temperature is 13.5 °C. Find out the amount	[L4][CO3]	[10M]

	of heat to be generated by the body per hour if $\rho = 1.025 \text{ kg/m}^3$ , $\nu = 15.06 \times 10^{-6} \text{ m}^2/\text{s}$ , $c_p = 0.96 \text{ kJ/kg}^\circ\text{C}$ and $k = 0.0892 \text{ kJ/mh }^\circ\text{C}$ and $\beta = 1/298 \text{ K}^{-1}$ . Assume $Nu = 0.12(\text{Gr.Pr})^{1/3}$ .		
<b>10</b>	Calculate the heat transfer from a 60 W incandescent bulb at $115^\circ\text{C}$ to ambient air at $25^\circ\text{C}$ . Assuming the bulb as a sphere of 50 mm diameter. Also, find the percentage of power lost by free convection. The correlation is given by: $Nu = 0.60 (\text{Gr.Pr})^{1/4}$	[L4][CO3]	[10M]


**SIDDARTHA INSTITUTE OF SCIENCE AND TECHNOLOGY, PUTTUR**

Siddharth Nagar, Narayanavanam Road – 517583

**QUESTION BANK (DESCRIPTIVE)**
**Subject with Code:** Heat & Mass Transfer (18ME0320)

**Branches:** ME

**Year & Sem:** III-B.Tech & I-Sem

**Regulation:** R18

**UNIT –IV**
**PHASE CHANGE HEAT TRANSFER AND HEAT EXCHANGERS**

1	a	What are limitations of LMTD method	[L1][CO4]	[2M]
	b	Define LMTD of a heat exchanger	[L1][CO4]	[2M]
	c	Describe plate heat exchangers.	[L2][CO4]	[2M]
	d	Define Boiling and Condensation.	[L1][CO4]	[2M]
	e	Which of the arrangement of heat exchangers (HEX) is better, (i) parallel flow,(ii) Counter flow. Explain the reasons	[L2][CO4]	[2M]
2		Explain briefly the various regimes of saturated pool boiling with diagram	[L3][CO4]	[10M]
3	a)	Mention correlation in boiling with proper expression	[L3][CO4]	[5M]
	b)	Discuss the different types of processes for condensation of vapours on a solid surface	[L3][CO4]	[5M]
4		Saturated steam at $t_{\text{sat}} = 90^{\circ}\text{C}$ ( $P = 70.14 \text{ kPa}$ ) condenses on the outer surface of a 1.5 m long 2.5 m OD vertical tube maintained at a uniform temperature $t_{\infty} = 70^{\circ}\text{C}$ . Assuming film condensation. Calculate i). The local transfer coefficient at the bottom of the tube, and ii). The average heat transfer coefficient over the entire length of the tube. Properties of water of $80^{\circ}\text{C}$ , $\rho_l = 974 \text{ kg/m}^3$ , $k_t = 0.668 \text{ W/mK}$ , $\mu_l = 0.335 \times 10^{-3} \text{ kg/m}^3$ , $h_{fg} = 2309 \text{ kJ/kg}$ , $\rho_v \ll \rho_l$	[L4][CO4]	[10M]
5	a)	What are the applications of boiling and condensation process?	[L1][CO4]	[4M]
	b)	A vertical tube of 60 mm outside diameter and 1.2 m long is exposed to steam at atmospheric pressure. The outer surface of the tube is maintained at a temperature of $50^{\circ}\text{C}$ by circulated cold water through the tube. Calculate the following i). The rate of heat transfer to the coolant, and ii). The rate of condensation of steam	[L4][CO4]	[6M]
6	a)	Differentiate between the mechanism of film wise and drop wise condensation	[L3][CO4]	[5M]
	b)	How are heat exchangers classified based on direction of fluid motion. explain with neat diagram	[L2][CO4]	[5M]
7		Derive the expression for Logarithmic Mean Temperature Difference (LMTD) in case of parallel flow	[L3][CO4]	[10M]
8		Derive the expression for Logarithmic Mean Temperature Difference (LMTD) in case of counter flow	[L3][CO4]	[10M]
9		The flow rate of hot and cold water streams running through a parallel flow heat exchanger are 0.2 kg/s and 0.5 kg/s respectively. The inlet temperatures on the hot and cold sides are $75^{\circ}\text{C}$ and $20^{\circ}\text{C}$ respectively. The exit temperature of hot water is $45^{\circ}\text{C}$ . If the individual heat transfer coefficients on the both sides are $650 \text{ W/m}^2 \text{ }^{\circ}\text{C}$ , calculate the area of heat exchanger.	[L4][CO4]	[10M]
10	a)	Distinguish between Boiling and Condensation	[L3][CO4]	[4M]
	b)	In a certain double pipe heat exchanger hot water flow at a rate of 5000 kg/h and gas cooled from $95^{\circ}\text{C}$ to $65^{\circ}\text{C}$ . At the same time 50000 kg/h of cooling water at $30^{\circ}\text{C}$ enters the heat exchanger. The flow conditions are that $L_{\text{overall}}$ heat transfer coefficient remains constant at $2270 \text{ W/m}^2 \text{ K}$ . Determine the heat transfer area required and the effectiveness, assuming two streams are in parallel flow. Assume for the both the streams $c_p = 4.2 \text{ kJ/kg K}$	[L4][CO4]	[6M]


**SIDDHARTHA INSTITUTE OF SCIENCE AND TECHNOLOGY, PUTTUR**

Siddharth Nagar, Narayanavanam Road – 517583

**QUESTION BANK (DESCRIPTIVE)**
**Subject with Code:** Heat & Mass Transfer (18ME0320)

**Branches:** ME

**Year & Sem:** III-B.Tech & I-Sem

**Regulation:** R18

**UNIT –V  
RADIATION AND MASS TRANSFER**

<b>1</b>	<b>a</b>	What is Block body?	[L1][CO5]	[2M]
	<b>b</b>	Define Mass transfer.	[L1][CO6]	[2M]
	<b>c</b>	State Stefan Boltzmann Law	[L1][CO5]	[2M]
	<b>d</b>	State Kirchoff's Law	[L1][CO5]	[2M]
	<b>e</b>	Define Radiation?	[L1][CO5]	[2M]
<b>2</b>	a)	What is black body ? How is differ from a gray body ?	[L1][CO5]	[6M]
	b)	Explain Stefan Boltzmann Law, Kirchoff's Law	[L1][CO5]	[4M]
<b>3</b>	The effective temperature of the body having an area of 0.12 m <sup>2</sup> is 527 °C. Calculate the following		[L4][CO5]	[10M]
	i)	The total rate of energy emission		
	ii)	The wave length of maximum monochromatic emissive power		
<b>4</b>	a)	Define the term absorptivity, reflectivity and transmittivity of radiation	[L1][CO5]	[4M]
	b)	Explain Plank's Law, Wiens Displacement Law.	[L2][CO5]	[6M]
<b>5</b>	Explain the surface emissive properties		[L2][CO5]	[10M]
<b>6</b>	a)	Explain the concept of black body	[L1][CO5]	[4M]
	b)	Assuming the sun to be a black body emitting radiation with maximum intensity at $\lambda = 0.49 \mu\text{m}$ , calculate the following	[L4][CO5]	[6M]
	i.	The surface temperature of the sun		
	ii.	The heat flux at surface of the sun		
<b>7</b>	Calculate the following for an industrial furnace in the form of black body and emitting radiation at 2500 °C.		[L4][CO5]	[10M]
	i.	Monochromatic emissive power at 1.2 $\mu\text{m}$ length		
	ii.	Wave length at which the emission is maximum		
	iii.	Maximum emissive power		
	iv.	Total emissive power		
	v.	Total emissive power of the furnace if the assumed as a real surface with emissivity equal to 0.9.		
<b>8</b>	a)	Explain the modes of Mass transfer	[L2][CO6]	[6M]
	b)	What is Mass transfer coefficient?	[L2][CO6]	[4M]
<b>9</b>	Define Fick's law. Explain briefly.		[L1][CO6]	[10M]
<b>10</b>	a)	Explain correlation for mass transfer	[L2][CO6]	[6M]
	b)	List out the application of Mass Transfer	[L1][CO6]	[4M]